

10/596588

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau(43) International Publication Date  
21 June 2007 (21.06.2007)

PCT

(10) International Publication Number  
**WO 2007/068147 A1**(51) International Patent Classification:  
G06F 9/445 (2006.01)MinHang District, Shanghai 200336 (CN). WANG, Jun  
[CN/CN]; 35#602, XinJin'San Cun, Changning District,  
Shanghai 200335 (CN).(21) International Application Number:  
PCT/CN2005/002231(74) Agent: CHINA PATENT AGENT (H.K.) LTD.; 22/F,  
Great Eagle Centre, 23 Harbour Road, Wanchai, Hong  
Kong (CN).(22) International Filing Date:  
17 December 2005 (17.12.2005)(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KM, KN, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV,  
LY, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI,  
NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG,  
SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US,  
UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language: English

(26) Publication Language: English


(71) Applicant (for all designated States except US): INTEL  
CORPORATION [US/US]; 2200 Mission College Blvd.,  
Santa Clara, CA 95052 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): XIE, Guohong  
[CN/CN]; 11#, 901 nong, Yuqing Road, Nanhui District,  
Shanghai 201315 (CN). YEO, Boon-Lock [US/US];  
28238 Christopher Lane, Los Altos Hills, CA 94022 (US).  
LI, Gangjiang [CN/CN]; Yaohong Road N0. 259, 17#401,(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,  
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

[Continued on next page]

(54) Title: INSTALLING AND EXECUTING SHARED APPLICATIONS IN SHARED FOLDERS



(57) Abstract: Provided are a method, system, and program for installing and executing shared applications in shared folders. A program is installed by a base computer, having a local storage, to a shared folder accessible to multiple client computers over a network. Installing the program adds files for the program to the shared folder and modifies the local device used by the base computer and enables the base computer to run the program by accessing the program files in the shared folder. An image is created of the local device of the base computer including the installed program. The image is provided to the client computers to apply to local devices of the client computers. Applying the image to the local devices of the client computers enables the client computers to access the program files in the shared folder to run the program.

WO 2007/068147 A1



European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— *with international search report*

## INSTALLING AND EXECUTING SHARED APPLICATIONS IN SHARED FOLDERS

### BACKGROUND

5 [0001] In certain network environments, such as Internet cafes, corporate settings, etc., all client systems are required to be loaded with an identical set of system programs (e.g., operating system and drivers) and software applications to provide a uniform environment for all the client computers. System provisioning is the process of installing the identical set of system and application programs on all the client  
10 computers to implement the uniform environment. System provisioning may be accomplished by first installing system components (e.g., the operating system, drivers, etc.) and the necessary applications onto a "golden computer". An image may then be taken of the golden computer storage having the installed programs. The identical image from the golden computer may then be loaded onto the local storage  
15 devices of the client computers as part of the system provisioning. The copending and commonly assigned patent application titled "Apparatus and Method For Incremental Package Deployment, having U.S. Application No. 11/027,870 and filed December 29, 2004, provides a technique for providing an installation of additional applications on the golden computer to the client computers in an incremental  
20 package.

[0002] One issue in implementing a uniform computing environment is the ever increasing size of application programs, which requires that the client computers provide sufficient storage space to store such large programs. Certain uniform environments, such as Internet cafes where users are provided access to numerous  
25 large computer video game programs and organizations that require access to many large business application programs, require that each client computer includes a substantial amount of storage to store the numerous large applications. Adding sufficient storage space to each of the client computers in such a uniform environment can be costly and substantially raise the cost per client machine and the cost to service  
30 the client storage devices.

**CONFIRMATION COPY**

### BRIEF DESCRIPTION OF THE DRAWINGS

- [0003] FIG. 1 illustrates an embodiment of a network computing environment.
- [0004] FIG. 2 illustrates an embodiment of components in a memory to access
- 5 components of shared applications in a shared folder.
- [0005] FIG. 3 illustrates an embodiment of how the shared folder directory file structure may map to a local directory file structure.
- [0006] FIG. 4 illustrates an embodiment of operations to deploy an image of a base (golden) computer to client computers in a network.
- 10 [0007] FIG. 5 illustrates an embodiment of operations to deploy additional incremental installations to a base (golden) computer to client computers in a network.
- [0008] FIG. 6 illustrates an embodiment of a diagram of how incremental installations to the base computer are deployed to the client computers.
- [0009] FIG. 7 illustrates an embodiment of components used to create and deploy the
- 15 base image and incremental packages.
- [0010] FIG. 8 illustrates an embodiment of operations to write to files in the shared folders.
- [0011] FIG. 9 illustrates an embodiment of how a file is divided into segments.
- [0012] FIG. 10 illustrates an embodiment of operations to read files in the shared
- 20 folders.
- [0013] FIG. 11 illustrates an embodiment of a computer architecture that may be used with the described embodiments.

### DETAILED DESCRIPTION

- 25 [0014] FIG. 1 illustrates an embodiment of a network computing environment. A base computer 2, also known as the golden computer, includes a processor 4, such as a central processing unit, and a memory 6, such as a volatile memory device used as the system 2 main memory. The base computer 2 has installed core programs 8, such as an operating system and device drivers, etc., and local shared application
- 30 components 10 for shared application programs 12 installed in a shared folder 14. During initialization, the core programs 8 may be loaded from the local storage 16 into the memory 6 and executed by the processor 4.
- [0015] The local shared application components 10 comprise those files and configuration settings installed at the base computer 2 when the base computer 2 is

used to install the shared applications 12 onto the shared folder 14. Local shared application components 10 installed at the base computer 2 may include library files, system files required when executing the shared applications 12, and configuration settings, such as registry file entries for the shared applications 12. During  
5 installation at the base computer 2 of shared applications 12 in the shared folder 14, most of the program files for the shared applications 12 may be stored in the shared folder 14, requiring only a much smaller set of local shared application components 10 to be installed and stored at the base computer 2.

**[0016]** A shared storage 18 is accessible to the base computer 2 and other client  
10 computers 20a...20n over a network 22. The shared storage 18 includes folders 14 having shared applications 12 installed by the base computer 2. The client computers 20a...20n include a processor 22a...22n, memory 24a...24n, and local storage 26a...26n, such as a hard disk drive or other storage devices. At some point, a base image 28 may be formed from all the files installed on the base computer 2, including  
15 the core programs 8 and files and settings 10. This base image 28 may be supplied to a server 30 over the network 22, and then deployed by a deployment program 32 executing in the server 30 as base images 28a...28n to the client computers 20a...20n to install at the client computers 20a...20n. The deployment program 32 may also deploy incremental packages of updates to the base image 28 to the client computers  
20 20a...20n.

**[0017]** The base 2 and client 20a...20n computers may be of a same type or configuration and deployed in an Internet café where the client computers 20a...20n are used to run computer games and other programs installed as shared applications 12 in the shared folder 14. The base 2 and client 20a...20n computers may exist in  
25 other network environments where similar client systems use a same set of application programs, such as a corporate environment or other organizational setting requiring a uniform computing environment.

**[0018]** The base 2 and client 20a...20n computers may comprise computing devices known in the art, such as desktop computers, laptops, servers, hand held computing  
30 devices, telephony devices, etc. The server 30 may comprise a server class machine. The network 22 may comprise a Local Area Network (LAN), Intranet, the Internet, Wide Area Network (WAN), peer-to-peer network, wireless network, etc. The shared storage 18 may comprise a suitable type of storage device or devices to store the shared applications 12 that may be accessed over the network 22, such as one or more

hard disk drives (e.g. an array of disks, such as a Redundant Array of Independent Disks (RAID)), flash memory, etc. In one embodiment, the server 30 may include a storage controller to manage access to the shared storage 18 or the shared storage 18 may comprise hard disk drives within the server 30.

5 [0019] FIG. 2 illustrates an embodiment of certain of the core programs 8 loaded into the memories 6, 24a...24n and used to manage read/write requests to shared application 12 components in the shared folders 14. An application 50 executing in a user mode portion of the memory 52, which may comprise the executable files for a shared application 12 accessed from the shared folders 14, may issue a read/write  
10 request directed to a file in the shared folder 14. The read/write request toward a shared file 54 in the shared folder 14 is first processed by a remote disk sharing driver 56 executing in a kernel mode 58. The remote disk sharing driver 56 may call a local file system driver 62 to execute the request against a local copy 60 of the requested shared file. If there is no local copy 60 of the requested shared file, then the remote  
15 disk sharing driver 56 calls a network file system driver 64 to access the requested shared file 54 from the shared folder 14 to then store as a local copy 60 in a local device, such as a hard disk drive 16, 26a...26n or a local memory 6, 24a...24n. The remote disk sharing driver 56 maintains a mapping 66 of shared files to local copies 58 of the shared files maintained in the local device. The drivers 56, 62, and 64 may  
20 be part of the core programs 8 included in the base computer images 28a...28n deployed at the client computers 20a...20n.

[0020] FIG. 3 illustrates an embodiment of the mapping 66 generated and used by the remote disk sharing driver 56 providing an association of shared files 54 having a local copy 60 in the local device. Shared file directory 70 comprises the file directory  
25 structure of the shared folders 14 in the shared storage 18. The local file directory 72 structure indicates the directory structure being generated by the remote disk sharing driver 56 in the local device as files are accessed from the shared storage 54 to provide locally as needed by executing applications 50. Thus, the remote disk sharing driver 56 may generate both the directory structure and files, because a file may be  
30 identified by its path as well as file name. The local file directory 72 is only a partial view of the shared file directory 70 if the remote disk sharing driver 56 has not accessed all shared files in the shared folders 14. The mapping 66 provides information 74 associating a shared file 76 with a local copy of the shared file 78. Thus, the mapping may comprises any suitable type of information, data structure,

pointer, etc. indicating an association of one shared file with a local copy of the shared file. If there is no mapping information for one shared file 78, then a local copy 78 has not yet been created for the shared file 78.

[0021] FIG. 4 illustrates an embodiment of operations performed at the base computer 2 and server 30 to install base images 28a...28n on the client computers 20a...20n. Upon beginning (at block 100) the process, an administrator installs (at block 102) an operating system, drivers and other core programs 8 on the base computer 2 that are not already installed. After the base computer 2 has the desired base installation, including core programs 8 and local shared application components 10, the administrator may mount (at block 104) the shared folder 14 with writing privileges, if it has not already been mounted, and then install (at block 106) shared application 12 programs on shared folders 18 from the base computer 2. This installation adds program files to the shared folders 18, such as the executable files and other related files and adds the local shared application components 10 (e.g., library files, system files, configuration settings, etc.) to the base computer 16. After the programs are installed, the administrator or a program, such as the deployment program 32, may apply (at block 108) a read-only setting to shared folders 14. An image 28 of the local storage 16 of the base computer 2 including the installed core programs 8 and local shared application components 10 is created (at block 110). The base image 28 is sent (at block 112) to the server 30, where the deployment program 32 deploys (at block 114) the base image 28 to the client computers 20a...20n to load into local storage 26a...26n and use as base images 28a...28n.

[0022] FIG. 5 illustrates an embodiment of operations to deploy applications installed in the shared folders 14 from the base computer 12 after the initial installation, such as application programs added at a later point as part of an upgrade. FIG. 6 illustrates the effect of the operations of FIG. 5 in the base 2 and client 20a...20n computers. With respect to FIG. 5, upon initiating (at block 130) operations to install new application in the shared folder 14 from the base computer 2, an administrator disables (at block 132) client computers 20a...20n access to the shared folders 14. The administrator then installs (at block 134) one or more additional program(s) or program upgrades on the shared folder 14 using the base computer 2. The base computer 2 includes a specialized disk driver 150 (FIG. 6) to redirect write requests during the installation to destination blocks 152 to redirection blocks 154, and indicate in the mapping table 156 those destination blocks 152 whose write data is

stored in the redirection blocks 154. Upon intercepting (at block 136) writes to base computer destination blocks 152 in memory 6, the disk driver 150 creates (at block 138) an entry in the mapping table 156 associating the destination blocks 152 to which the write is directed to redirected blocks 154 if there is no preexisting entry for the target destination blocks 152. The writes are then applied (at block 140) to the redirected blocks 154. If (at block 142) installation has not completed, then control returns to block 136 to process further writes. Otherwise, if installation has completed, then an incremental package 158 is formed (at block 144) including copies 154' and 156' of the redirected blocks 154 and mapping table 156, respectively, having writes made to the base computer memory 6 during the application upgrade installation. The incremental package 158 is supplied to the server deployment program 32 which then deploys (at block 146) the incremental package 158 to the client computers 20a...20n to commit (at block 148) the redirected blocks 154a...154n loaded into the client memories 24a...24n to the destination blocks 152a...152n in the client memories 24a...24n using the mapping tables 156a...156n. Instances 158a...158n of incremental package 158 are supplied to the client computers 20a...20n, each instance 158a...158n including redirected blocks 154a...154n and the mapping tables 156a...156n. At some point, the writes from the update to the base computer 2 are then moved from the destination blocks 152a...152n in the memories 24a...24n to the non-volatile copy in local storage 26a...26n.

[0023] With the embodiments of FIGs. 4, 5, and 6, an administrator may first install application and system programs on the base (golden) 2 to perfect and test the installation. An image of the entire base (golden) computer 2 may then be provided to load onto the client computer local storages 26a...26n. Further, an incremental package 158 of application related components added, e.g., libraries, etc., added to the base computer 2 during an upgrade to the shared applications 12 may be provided to the client computers 20a...20n to load. In this way, most of the shared application 12 components and files are maintained in the shared folders 14, and only certain application components 10, e.g., registry entries, system files, are added to the client computers 20a...20n to use to access and run the shared applications 12. This conserves the amount of space used by the local storage 26a...26n.

[0024] FIG. 7 illustrates an embodiment of components implemented in the base computer 2 and or server 30 to perform the image creation and deployment operations of FIGs. 4, 5, and 6. The base computer 2 is provided one or more installation



programs 170 that run on the base computer 2 and are installed on the base computer and/or shared folders 14. The installation program 170 may perform the operations at blocks 102, 104, and 106 of FIG. 4. An image program 174, which may execute on the base computer 2 or the server 30, creates an image of the contents of the local storage 16, or base image 28 (FIG. 1). The image program 174 may perform the operation at blocks 110 and 112 in FIG. 4. A deployment program 180 that runs on the server 30, or alternatively on the base computer 2, may deploy the base image 2 to the client computers 20a...20n as base images 28a...28n. An incremental package program 176 may comprise the disk driver 150 (FIG. 6) to perform the operations of FIG. 5, e.g., operations 152, 154, 156, 158, 160, 162, and 165, to create an incremental package 158 including redirected blocks 154' and mapping table 156'. The incremental package deployment program 180 may deploy the incremental package 158 to the client computers 20a...20n by performing the operations at block 166 in FIG. 5.

[0025] FIG. 8 illustrates an embodiment of operations performed by the remote disk sharing driver 56 during operations the client computers 20a...20n perform to write data to the files for the shared applications 12 in the shared folders 14. The remote disk sharing driver 56 intercepts (at block 200) a write request from an executing application 50 to a requested shared file in the shared folder 14. The remote disk sharing driver 56 determines (at block 202) whether the mapping 66 provides a mapping of the requested shared file 54 (FIG. 2) to a local copy 60 of the shared file. If so, then the remote disk sharing driver 56 writes (at block 204) the update to the local copy 60 of the shared file, updating segment(s) including the modified data. FIG. 9 shows that a local copy of a file 230 in the memory 24a...24n is comprised of a plurality of segments 232a...232n and includes file metadata 234, such as the number of segments 232a...232n, the number of empty segments and/or segments including data. If (at block 202) there is no local copy 60, then the remote disk sharing driver 56 generates (at block 206) a mapping 74 (FIG. 3) in the mapping 66 of the shared file to a local copy 60 of the shared file. Control then proceeds to block 204 to write the write data to one or more segments 232a...232n in the local copy of the shared file 60.

[0026] With the embodiments of FIGs. 8 and 9, the client computers 20a...20n do not alter the contents of the shared folders 14 because all writes to segments of the application 12 components and files in the shared folders 14 are stored and

maintained locally. This avoids any write conflicts to the shared folder 14 when the clients are executing shared applications 12 from the shared folders 14.

[0027] FIG. 10 illustrates operations performed by the remote disk sharing driver 56 during operations the client computers 20a...20n perform to read data from the files for the shared applications 12 in the shared folders 14. Upon intercepting (at block 250) a read request to a requested shared file in the shared folder 14, the remote disk sharing driver 56 determines (at block 252) whether the mapping 66 includes a mapping of the shared file 54 to a local copy 60 of the shared file. If so, then a determination is made (at block 254) whether the local copy 60 of the requested shared file includes the segment(s) 232a...232n having the requested data. If (at block 254) the requested segments are not in a local device, e.g., storage 26a...26n or memory 24a...24n, then the remote disk sharing driver 56 accesses (at block 256) the at least one segment 232a...232n including the requested data from the requested shared file 230 in the shared folder 14 over the network 22 and stores (at block 258) the accessed segment 232a...232n in the local copy 60 of the shared file. If there is already data for the accessed segment 232a...232n at the local device, then the requested data accessed from the shared folder may be combined with the data already in the accessed segment 232a...232n.

[0028] If (at block 254) the requested segments 232a...232n are in the local device, then data for the read request is accessed (at block 260) from the local copy 60. From block 258 or 260, control proceeds to block 262 to return the accessed data to the read request. If (at block 252) there is no mapping 74 (FIG. 3) in the mappings 66 of the requested shared file to a local copy 60, then the remote disk sharing driver 56 generates (at block 264) a mapping 74 (FIG. 3) of the requested shared file 54 to a local copy 60 of the requested shared file in the local device (e.g., memory 24a...24n or storage 26a...26n). Control then proceeds to block 256 to access the data locally to return.

[0029] In further embodiments, the remote disk sharing driver 56 may limit the number of shared files stored locally by deleting local copies 60 on a Last-in-First-Out (LIFO) or least frequently used basis.

[0030] With the operations of FIG. 10, segments of shared files 54 in the shared folder 14 are accessed over the network 22 as needed and stored locally to return to read requests. The segments accessed from the shared folders 14 may comprise components of shared applications 12, such as executable files and files used by the

executable file, e.g., dynamic linked libraries, images, video, etc. Further, because the client computers 20a...20n only have read access to the shared folders 14 and maintain writes to components of shared application 12 in a local device (e.g., memory 24a...24n or storage 26a...26n) the risk of a conflicting write operation to the shared folders 14 delaying a client's access of a file is substantially reduced. Further, maintaining segments of shared components locally allows for faster local access to those portions of the shared applications 12 accessed frequently. Yet further, downloading components only as needed conserves storage space at the local storage 26a...26n, while at the same time providing access to many shared applications 12 whose direct installation on the client computers 20a...20n would require additional storage space at the client computers.

[0031] The described operations may be implemented as a method, apparatus or article of manufacture using standard programming and/or engineering techniques to produce software, firmware, hardware, or any combination thereof. The described operations may be implemented as code maintained in a "computer readable medium", where a processor may read and execute the code from the computer readable medium. A computer readable medium may comprise media such as magnetic storage medium (e.g., hard disk drives, floppy disks, tape, etc.), optical storage (CD-ROMs, DVDs, optical disks, etc.), volatile and non-volatile memory devices (e.g., EEPROMs, ROMs, PROMs, RAMs, DRAMs, SRAMs, Flash Memory, firmware, programmable logic, etc.), etc. The code implementing the described operations may further be implemented in hardware logic (e.g., an integrated circuit chip, Programmable Gate Array (PGA), Application Specific Integrated Circuit (ASIC), etc.). Still further, the code implementing the described operations may be implemented in "transmission signals", where transmission signals may propagate through space or through a transmission media, such as an optical fiber, copper wire, etc. The transmission signals in which the code or logic is encoded may further comprise a wireless signal, satellite transmission, radio waves, infrared signals, Bluetooth, etc. The transmission signals in which the code or logic is encoded is capable of being transmitted by a transmitting station and received by a receiving station, where the code or logic encoded in the transmission signal may be decoded and stored in hardware or a computer readable medium at the receiving and transmitting stations or devices. An "article of manufacture" comprises computer readable medium, hardware logic, and/or transmission signals in which code may be

implemented. A device in which the code implementing the described embodiments of operations is encoded may comprise a computer readable medium or hardware logic. Of course, those skilled in the art will recognize that many modifications may be made to this configuration without departing from the scope of the present  
5 invention, and that the article of manufacture may comprise suitable information bearing medium known in the art.

[0032] FIG. 11 illustrates an embodiment of a computer architecture 300 that may be implemented at the base 2 and client 20a...20n computers. The architecture 300 may include a processor 302 (e.g., a microprocessor), a memory 304 (e.g., a volatile  
10 memory device), and storage 306 (e.g., a non-volatile storage, such as magnetic disk drives, optical disk drives, a tape drive, etc.). The storage 306 may comprise an internal storage device or an attached or network accessible storage. Programs, including an operating system 308 and application programs, in the storage 306 are loaded into the memory 304 and executed by the processor 302 in a manner known in  
15 the art. The architecture further includes a network card 310 to enable communication with a network. An input device 312 is used to provide user input to the processor 302, and may include a keyboard, mouse, pen-stylus, microphone, touch sensitive display screen, or any other activation or input mechanism known in the art. An output device 314 is capable of rendering information transmitted from the  
20 processor 302, or other component, such as a display monitor, printer, storage, etc.

[0033] The terms "an embodiment", "embodiment", "embodiments", "the embodiment", "the embodiments", "one or more embodiments", "some embodiments", and "one embodiment" mean "one or more (but not all) embodiments of the present invention(s)" unless expressly specified otherwise.

25 [0034] The terms "including", "comprising", "having" and variations thereof mean "including but not limited to", unless expressly specified otherwise.

[0035] The enumerated listing of items does not imply that any or all of the items are mutually exclusive, unless expressly specified otherwise.

[0036] The variable "n" when used to represent a variable number of an element, e.g.,  
30 20a...20n, 232a...32n, etc., may indicate any number of instances of the element, and may indicate different integer numbers when used with different elements or with the same element in different instances.

[0037] The terms "a", "an" and "the" mean "one or more", unless expressly specified otherwise.

[0038] Devices that are in communication with each other need not be in continuous communication with each other, unless expressly specified otherwise. In addition, devices that are in communication with each other may communicate directly or indirectly through one or more intermediaries.

- 5 [0039] A description of an embodiment with several components in communication with each other does not imply that all such components are required. On the contrary a variety of optional components are described to illustrate the wide variety of possible embodiments of the present invention.

- 10 [0040] Further, although process steps, method steps, algorithms or the like may be described in a sequential order, such processes, methods and algorithms may be configured to work in alternate orders. In other words, any sequence or order of steps that may be described does not necessarily indicate a requirement that the steps be performed in that order. The steps of processes described herein may be performed in any order practical. Further, some steps may be performed simultaneously.

- 15 [0041] When a single device or article is described herein, it will be readily apparent that more than one device/article (whether or not they cooperate) may be used in place of a single device/article. Similarly, where more than one device or article is described herein (whether or not they cooperate), it will be readily apparent that a single device/article may be used in place of the more than one device or article or  
20 that a different number of devices may be used than the multiple number shown.

[0042] The functionality and/or the features of a device may be alternatively embodied by one or more other devices which are not explicitly described as having such functionality/features. Thus, other embodiments of the present invention need not include the device itself.

- 25 [0043] The illustrated operations of FIGs. 4, 5, 8, and 10 show certain events occurring in a certain order. In alternative embodiments, certain operations may be performed in a different order, modified or removed. Moreover, steps may be added to the above described logic and still conform to the described embodiments. Further, operations described herein may occur sequentially or certain operations may be  
30 processed in parallel. Yet further, operations may be performed by a single processing unit or by distributed processing units.

[0044] The foregoing description of various embodiments of the invention has been presented for the purposes of illustration and description. It is not intended to be exhaustive or to limit the invention to the precise form disclosed. Many modifications

and variations are possible in light of the above teaching. It is intended that the scope of the invention be limited not by this detailed description, but rather by the claims appended hereto. The above specification, examples and data provide a complete description of the manufacture and use of the composition of the invention. Since  
5 many embodiments of the invention can be made without departing from the spirit and scope of the invention, the invention resides in the claims hereinafter appended.

WHAT IS CLAIMED IS:

- 1           1.       A method to create an image to deploy to client computers that  
2       communicate over a network, comprising:  
3           installing a program with a base computer, having a local storage, wherein the  
4       base computer is adapted to access to a shared folder accessible to the client  
5       computers over a network, wherein installing the program adds files for the program  
6       to the shared folder and modifies the local device used by the base computer, and  
7       wherein installing the program enables the base computer to run the program by  
8       accessing the program files in the shared folder;  
9           creating an image of the local device of the base computer including the  
10       installed program; and  
11          providing the image to the client computers to apply to local devices of the  
12       client computers, wherein applying the image to the local devices of the client  
13       computers enables the client computers to access the program files in the shared  
14       folder to run the program.
- 1           2.       The method of claim 1, wherein modifying the local device comprises  
2       modifying configuration settings for the base computer stored in the local device and  
3       adding files to the local device.
- 1           3.       The method of claim 1, wherein the program comprises a first program,  
2       further comprising:  
3           installing a second program on the base computer to the shared folder, wherein  
4       installing the second program adds files for the second program to the shared folder  
5       and modifies memory of the base computer, and wherein installing the second  
6       program enables the base computer to run the second program by accessing the  
7       program files in the shared folder;  
8           determining writes to the base computer memory during installation of the  
9       second program on the base computer; and  
10          providing the determined writes to the client computers to apply to the client  
11       computers, wherein the writes applied to the base computer memory during the  
12       installation of the second program are applied to the client computers, and wherein  
13       applying the writes to the client computers enables the client computers to access the  
14       second program files in the shared folder to run the second program..

1           4.     The method of claim 1, further comprising:  
2           setting the shared folder to read-only after installing the program to the shared  
3     folder.

1           5.     The method 1, wherein the image includes a driver that when loaded  
2     into the client computers causes the client computers to perform:  
3           intercepting a write request to a requested shared file in the shared folder;  
4           generate a mapping of the shared file to a local copy of the shared file in a  
5     local device; and  
6           applying the write to the local copy of the shared file.

1           6.     The method of claim 1, wherein the image includes a driver that when  
2     loaded into the client computers causes the client computers to perform:  
3           intercepting a read request to a requested shared file in the shared folder;  
4           determining whether there is a mapping of the requested shared file to a local  
5     copy of the requested shared file;  
6           accessing data for the read request from the local copy of the requested shared  
7     file in response to determining that there is the mapping of the requested shared file to  
8     the local copy; and  
9           accessing data for the read request from the requested shared file in the shared  
10    folder over the network in response to determining that there is no mapping of the  
11    requested shared file to the local copy.

1           7.     A method for accessing shared files in a shared folder over a network,  
2     comprising:  
3           enabling access to the shared folder accessible over the network;  
4           intercepting a write directed to one of the shared files in the shared folder;  
5           generating a mapping of the shared file to a local copy of the shared file in a  
6     local device; and  
7           applying the write to the local copy of the shared file.

1           8.     The method of claim 7, wherein the write to the local copy in the local  
2     device includes only a portion of the shared file, wherein the shared file and the local



3 copy of the shared file comprises of a plurality of segments, and wherein applying the  
4 write comprises:  
5 applying the write to update at least one of the segments of the local copy  
6 shared.

1 9. The method of claim 7, further comprising:  
2 receiving a read request to a requested shared file in the shared folder;  
3 determining whether there is a mapping of the requested shared file to a local  
4 copy of the requested shared file;  
5 accessing data for the read request from the local copy of the requested shared  
6 file in response to determining that there is the mapping of the requested shared file to  
7 the local copy; and  
8 accessing data for the read request from the requested shared file in the shared  
9 folder over the network in response to determining that there is no mapping of the  
10 requested shared file to the local copy.

1 10. The method of claim 9, further comprising:  
2 generating a mapping of the requested shared file to a local copy of the  
3 requested shared file in the local device in response to determining that there is no  
4 mapping of the requested shared file to the local copy; and  
5 copying the accessed data from the requested shared file to the local copy of  
6 the shared file in the local storage.

1 11. The method of claim 10, wherein the accessed data comprises one of a  
2 plurality of segments of the requested shared file, and wherein copying the accessed  
3 data to the local copy of the requested shared file comprises copying the accessed  
4 segment to the local copy of the shared file in the local device.

1 12. The method of claim 11, wherein the read request is for requested data  
2 in one of the segments of the requested shared file, further comprising:  
3 determining whether the local copy of the requested shared file includes the  
4 segment having the requested data in response to determining that there is the  
5 mapping of the requested shared file to the local copy;

6           accessing data from the segment including the requested data in the requested  
7   shared file in the shared folder over the network;  
8           returning the requested data from the accessed segment; and  
9           storing the accessed segment in the local copy of the requested shared file.

1           13.    The method of claim 12, wherein storing the accessed segment in the  
2   local copy further comprises:  
3           determining whether the local copy includes data for the accessed segment;  
4           applying the data in the local copy to the accessed segment to form a modified  
5   segment in response to determining that the local copy includes data for the accessed  
6   segment;  
7           storing the modified segment in the local copy in response to forming the  
8   modified segment; and  
9           storing the accessed segment in the local copy in response to determining that  
10   the local copy does not include data for the accessed segment.

1           14.    A system for creating an image to deploy to client computers that  
2   communicate over a network, comprising:  
3           a base computer, having a local storage and adapted to access a shared folder  
4   over a network, wherein a plurality of client computers are additionally adapted to  
5   access the shared folder over the network;  
6           an installation program adapted to be executed in the base computer to add  
7   files for a program to the shared folder, wherein the installation program modifies the  
8   local device used by the base computer to enable the base computer to run the  
9   program by accessing the program files in the shared folder;  
10          an image creation program adapted to create an image of the local device of  
11   the base computer including the installed program; and  
12          a deployment program adapted to communicate the image to the client  
13   computers over the network to apply to local devices of the client computers, wherein  
14   applying the image to the local devices of the client computers enables the client  
15   computers to access the program files in the shared folder to run the program.

1           15.     The system of claim 14, wherein modifying the local device comprises  
2     modifying configuration settings for the base computer stored in the local device and  
3     adding files to the local device.

1           16.     The system of claim 14, wherein the installed program comprises a  
2     first program, wherein the installation program comprises a first installation program,  
3     further comprising:

4           a second installation program adapted to install a second program on the base  
5     computer to the shared folder, wherein installing the second program adds files for the  
6     second program to the shared folder and modifies memory of the base computer, and  
7     wherein installing the second program enables the base computer to run the second  
8     program by accessing the program files in the shared folder;

9           an incremental package program adapted to determine writes to the base  
10    computer memory during installation of the second program on the base computer;  
11    and

12          an incremental deployment program adapted to provide the determined writes  
13    to the client computers to apply to the client computers, wherein the writes applied to  
14    the base computer memory during the installation of the second program are applied  
15    to the client computers, and wherein applying the writes to the client computers  
16    enables the client computers to access the second program files in the shared folder to  
17    run the second program.

1           17.     The system of claim 14, wherein the shared folder is set to read-only  
2     after installing the program to the shared folder.

1           18.     The system of claim 14, wherein the created image includes a driver  
2     that when loaded into the client computers is adapted to cause the client computers to  
3     perform:

4           intercepting a write request to a requested shared file in the shared folder;  
5           generate a mapping of the shared file to a local copy of the shared file in a  
6     local device; and  
7           applying the write to the local copy of the shared file.

1           19.     The system of claim 14, wherein the image includes a driver that when  
2 loaded into the client computers causes the client computers to perform:  
3           intercepting a read request to a requested shared file in the shared folder;  
4           determining whether there is a mapping of the requested shared file to a local  
5 copy of the requested shared file;  
6           accessing data for the read request from the local copy of the requested shared  
7 file in response to determining that there is the mapping of the requested shared file to  
8 the local copy; and  
9           accessing data for the read request from the requested shared file in the shared  
10 folder over the network in response to determining that there is no mapping of the  
11 requested shared file to the local copy.

1           20.     A system for accessing shared files in a shared folder over a network,  
2 comprising:  
3           a computer adapted to communicate with a local device coupled to the  
4 computer and adapted to communicate with the shared folder over the network,  
5 wherein the shared folder includes shared files;  
6           a network file system driver executed in the computer and adapted to access  
7 the shared folder over the network;  
8           a remote disk sharing driver executed in the computer and adapted to intercept  
9 a write directed to one of the shared files in the shared folder and generate a mapping  
10 of the shared file to a local copy of the shared file in the local device; and  
11           a local file system driver executed in the computer and adapted to apply the  
12 write to the local copy of the shared file.

1           21.     The system of claim 19, wherein the write to the local copy in the local  
2 device includes only a portion of the shared file, wherein the shared file and the local  
3 copy of the shared file comprises of a plurality of segments, and wherein the local file  
4 system driver is adapted to apply the write by updating at least one of the segments of  
5 the local copy shared.

1           22.     The system of claim 20,  
2           wherein the remote disk sharing driver is further adapted to receive a read  
3 request to a requested shared file in the shared folder, determine whether there is a  
4 mapping of the requested shared file to a local copy of the requested shared file;  
5           wherein the local file system driver is further adapted to access data for the  
6 read request from the local copy of the requested shared file in response to the remote  
7 disk sharing driver determining that there is the mapping of the requested shared file  
8 to the local copy; and  
9           wherein the network file system driver is further adapted to access data for the  
10 read request from the requested shared file in the shared folder over the network in  
11 response to the remote disk sharing driver determining that there is no mapping of the  
12 requested shared file to the local copy.

1           23.     The system of claim 22,  
2           wherein the remote disk sharing driver is further adapted to generate a  
3 mapping of the requested shared file to a local copy of the requested shared file in the  
4 local device in response to determining that there is no mapping of the requested  
5 shared file to the local copy; and  
6           wherein the network file system driver is further adapted to copy the accessed  
7 data from the requested shared file to the local copy of the shared file in the local  
8 storage.

1           24.     The system of claim 23, wherein the accessed data comprises one of a  
2 plurality of segments of the requested shared file, and wherein copying the accessed  
3 data to the local copy of the requested shared file comprises copying the accessed  
4 segment to the local copy of the shared file in the local device.

1           25.     The system of claim 24, wherein the read request is for requested data  
2 in one of the segments of the requested shared file,  
3           wherein the remote disk sharing driver is further adapted to determine whether  
4 the local copy of the requested shared file includes the segment having the requested  
5 data in response to determining that there is the mapping of the requested shared file  
6 to the local copy;

7        wherein the network file system driver is further adapted to access data from  
8        the segment including the requested data in the requested shared file in the shared  
9        folder over the network, return the requested data from the accessed segment, and  
10       store the accessed segment in the local copy of the requested shared file.

1           26.     The system of claim 25, wherein the read request is for requested data  
2        in one of the segments of the requested shared file,  
3           wherein the remote disk sharing driver is further adapted to determine whether  
4        the local copy of the requested shared file includes the segment having the requested  
5        data in response to determining that there is the mapping of the requested shared file  
6        to the local copy; and  
7           wherein the network file system driver is adapted to access data from the  
8        segment including the requested data in the requested shared file in the shared folder  
9        over the network, return the requested data from the accessed segment, and enable the  
10       storing of the accessed segment in the local copy of the requested shared file.

FIG. 1




FIG. 2






FIG.3




FIG. 4





FIG. 5



6/10





FIG. 6

FIG. 7



8/10

FIG. 8




FIG. 9




FIG. 10





FIG. 11





# INTERNATIONAL SEARCH REPORT

International application No.

PCT/CN2005/002231

## A. CLASSIFICATION OF SUBJECT MATTER

G06F 9/445(2006.01)i

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

G06F 9/(2006.01) i

G06F17/(2006.01) i

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)WPI  
EPODOC PATENTPIC PAJ CNPAT install+, share?, folder, client, program, network, computer, access+, image, intercept+, map+, file

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP1492028A1 (NEC CORP) 29.Dec 2004(29.12.2004) the whole documents	1-26
A	US6618857B1 (MICROSOFT CORP) 09.Sep 2003( 09.09.2003 ) the whole documents	1-26
A	US20040025154A1 ( SEDLACK D J ) 05.Feb 2004( 05.02.2004) the whole documents	1-26

☐ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

\* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim (S) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&"document member of the same patent family

Date of the actual completion of the international search  
17.Jul 2006(17.07.2006)

Date of mailing of the international search report

10 . AUG 2006 (10 . 08 . 2006)

Name and mailing address of the ISA/CN  
The State Intellectual Property Office, the P.R.China  
6 Xitucheng Rd., Jimen Bridge, Haidian District, Beijing, China  
100088  
Facsimile No. 86-10-62019451

Authorized officer

Telephone No. 86-10-62084944



**INTERNATIONAL SEARCH REPORT**  
Information on patent family members

International application No.  
PCT/CN2005/002231

Patent Documents referred in the Report	Publication Date	Patent Family	Publication Date
EP1492028A1	29.Dec 2004(29.12.2004)	US2004267754 A1	30.Dec 2004 ( 30.12.2004 )
		JP2005018643 A	20.Jan 2005(20.01.2005)
US6618857B1	09.Sep 2003( 09.09.2003 )	none	
US20040025154A1	05.Feb 2004( 05.02.2004)	none	